

# AMPLIROLL® HOOKLIFT AL26 PA



FASSI GROUP

## AMPLIROLL® TELESCOPIC & ARTICULATED JIB – 26T CAPACITY



### Hooklift with telescopic and articulated jib – Marrel range

Truck GVW from 26 to 32T				S49	S50	S51	S52	S53	S54	S55	S56	S57	S58	S59	S60
	Container length : min	LG	mm	3700	3700	3700	3700	4100	4100	4100	4100	4100	4600	4600	4600
	max			6100	6200	6300	6400	6500	6600	6700	6800	6900	7000	7100	7200
	Container with fixed underride	LG	mm	5400	5500	5600	5700	5800	5900	6000	6100	6200	6300	6400	6500
	Own weight			Kg	2740	2750	2750	2750	2790	2810	2810	2810	2930	2940	2940

Truck GVW from 26 to 32T				SL61	SL62	SL63	SL64	SL65	SL66	SL67	SL68
	Container length : min	LG	mm	4600	4600	4600	5000	5000	5000	5000	5000
	max			7300	7400	7500	7600	7700	7800	7900	8000
	Container with fixed underride	LG	mm	6600	6700	6800	6900	7000	7100	7200	7300
	Own weight			Kg	2980	3010	3040	3070	3100	3130	3160

Indicated figures are for information only and can be changed without prior notice.

### Key points

- Reducing the loading angle
- Larger range of container length
- Hook with pneumatic safety latch
- MARREL free tilting frame : unique concept that acts as a power multiplier and provides an unmatched lifting capacity
- Anticorrosion treatment : shot blasting and painting before component assembly
- Pre-drilled subframe : mounting with attachment brackets adapted to most of the trucks, out of a large catalog of accessories
- Available controls : pneumatic, electro-pneumatic, radio control
- Optimized height of the equipment ensures a low center of gravity
- Integrated dashpot in main cylinder for end of stroke damping

#### Hydraulics

- Hydraulic cylinders manufactured by Marrel
- Check valve for main cylinder
- Safety device to prevent miss-use of the equipment

#### Mechanical structure

- Steel with high tensile strength
- Casting parts used for critical functions
- Welding by robot welders and machining of the articulations

#### Safety and container locking

- Rear hydraulic body locking (outside and inside)
- In operation outside warning buzzer



## Options and Accessories

- Additional hydraulic valves (for cranes, rear tipper trailer, ...)
- Fast speed operation (only for moving empty bodies)
- Front hydraulic body locking device
- Rear axle suspension blocking synchronized with rear lock
- Rear stabilizer with independant controls and warning light
- Electro-pneumatical cab controls, ...

- Oil tank to be installed on truck sides or behind the cab
- Attachments brackets suited for the various truck model
- Rear under ride bumper PANTO, tiltable or fixed
- Side protections fixed or tiltable mount
- Tool box and expandable net carrier
- Fire extinguisher box – Working light
- Aluminium fender, ...



**marrel**

FASSI GROUP

Rond-Point Auguste Colonna  
B.P. 70056  
42161 Andrézieux-Bouthéon  
+33 (0)4 77 36 28 28



Edition : November 2018

Your Dealer