

# AMPLIROLL® HOOKLIFT AL24



FASSI GROUP

## AMPLIROLL® TELESCOPIC JIB –24T CAPACITY



### Hooklift with telescopic jib – Marrel range

Truck GVW from 26 to 32T			S49	S50	S51	S52	S53	S54	S55	S56	S57	S58	S59	S60
	Container length : min	LG mm	4300	4300	4300	4300	4700	4700	4700	4700	4700	5200	5200	5200
	Container length : max		6000	6100	6200	6300	6400	6400	6500	6600	6700	6800	6900	7000
	Container with fixed underride		5400	5500	5600	5700	5800	5900	6000	6100	6200	6300	6400	6500
	Own weight	Kg	2550	2560	2560	2560	2600	2620	2620	2620	2740	2750	2750	2760

Truck GVW from 26 to 32T			SL61	SL62	SL63	SL64	SL65	SL66	SL67	SL68
	Container length : min	LG mm	5200	5200	5200	5600	5600	5600	5600	5600
	Container length : max		7300	7400	7500	7600	7700	7800	7900	8000
	Container with fixed underride		6600	6700	6800	6900	7000	7100	7200	7300
	Own weight	Kg	2790	2820	2850	2880	2910	2940	2970	3000

Indicated figures are for information only and can be changed without prior notice.

### Key points

- Removable hook without safety latch
- MARREL free tilting frame : unique concept that acts as a power multiplier and provides an unmatched lifting capacity
- Anticorrosion treatment: shot blasting and painting before component assembly
- Pre-drilled subframe : mounting with attachment brackets adapted to most of the trucks, out of a large catalog of accessories
- Available controls : pneumatic, electro-pneumatique, radio control
- Optimized height of the equipment ensures a low center of gravity
- Integrated dashpot in main cylinders for end of stroke damping

#### Hydraulics

- Hydraulic cylinders manufactured by Marrel
- Check valve for main cylinder
- Safety device to prevent miss-use of the equipment

#### Mechanical structure

- Steel with high tensile strength
- Casting parts used for critical functions
- Welding by robot welders and machining of the articulations

#### Safety and container locking

- Rear hydraulic body locking (outside and inside)
- In operation outside warning buzzer
- Longitudinal stop on hook arm



## Options and Accessories

- Additional hydraulic valves (for cranes, rear tipper trailer, ...)
- Fast speed operation (only for moving empty bodies)
- Hook with mechanical or pneumatic safety latch
- Front hydraulic body locking device
- Rear axle suspension blocking synchronized with rear lock
- Rear stabilizer with independant controls and warning light
- Electro-pneumatical cab controls, ...

- Oil tank to be installed on truck sides or behind the cab
- Attachments brackets suited for the various truck model
- Rear under ride bumper PANTO, tiltable or fixed
- Side protections fixed or tiltable mount
- Tool box and expandable net carrier
- Fire extinguisher box – Working light
- Aluminium fender, ...



**marrel**

FASSI GROUP

Rond-Point Auguste Colonna  
B.P. 70056  
42161 Andrézieux-Bouthéon  
+33 (0)4 77 36 28 28



Edition : November 2018

Your Dealer